24-Track audio mixer-recorder

240 x 320 x 90 mm

Not only the best tool, but simple to use

Analog Inputs

Digital In/Out

CantarX3

Specifications

Dimensions

 $(w \times h \times d)$

Weight

| Analog inputs | 8 low noise mic preamps with very high quality transformer. 48V Phantom, limiters and filters 4 analog line inputs |
|-----------------|---|
| Digital inputs | AES digital inputs incude 2 AES42 pairs, 8 AES/EBU 32 Dante Audinate audio inputs |
| Analog outputs | 8 analog line level outputs |
| Digital outputs | 12 AES Digital outputs 32 Dante Audinate audio outputs |
| Routing | All inputs can be connected simultaneously All inputs can be routed to any of the tracks Mixdown can be assigned to any tracks Linear control faders and pot knobs are user assignable to Mixdown, inputs gain and outputs gain |
| Recording media | 1 x 256 GB SSD Drive 2 x SD Cards 1 x USB2 slot (all media can record simultaneously) |
| Connectivity | 4 x Balanced Analog XLR-3Mic/Line 4 x Balanced Analog XLR-5 Mic/Line or Line Only 1 x Hirose 4 pins (DC Out) 2 x DB25 (Balanced Analog Out / AES I/O) 2 x TA3M (AES42 Mode 2) 2 x Ethernet (1 Audinate Dante, 1 PC) 1 x 6.35mm (Headphones) 1 x 3.5mm (External slate mic input/Headphone) 1 x XLR4 (DC Input) 3 x USB2 slot 1 x DVI (External Video Monitor) 1 x 26 Pin 3M (accessories, world clock I/O) 1 x Lemo 5 (TimeCode) |
| Main features | - Broadcast Wave File recording - Metadata entry of Scene, Take, Notes, Track Names, and more - Self-Generated PDF and CSV Sound Reports embedded with deliverable media - Ultra bright and wide display panel - New improved interface menu accessible through buttons and jog wheel - All inputs and outputs monitoring and routing accessible through intuitive menus Enhanced Playback Monitoring with Waveform Display on front panel - Rec&Play: Record live audio while playing back pre-recorded files - Ultra efficient analog limiters - Variable Delay on all analog Inputs and Outputs - AutoSlate clap detection and logging - High Precision 1ppm Timecode generator - 30 Seconds Pre-Record Buffer |
| Power | 2 smart Lithium Ion batteries 14,4V-3,4Ah and / or XLR4 12 - 17V DC |
| Data link | Wi-fi / Ethernet (Metadata edition, file transfer) |

9.4 x 12.6 x 3.5 inches

With batteries 8.8 lbs, 4,01 kg | Without batteries 7.8 lbs, 3.55 kg